








## APPLICATION CHART

	DPG125	DCDA125	DCDW125	DCDS125	DCDV125	DCW60
Dry Use 	●	●	●	●	●	●
Wet Use 	●	●	●	●	●	●
Porcelain Tiles	●	●	●	●	●	●
Ceramic Tiles		●	●	●	●	●
Slate		●		●	●	
Marble			●			●
Granite						
Terracotta		●	●	●		
Concrete						
Glazed Clinker				●		
Hard Tile		●			●	
Slim Slab	●	●	●	●		
Big Slab	●	●	●	●		
Mosaic Tiles				●		
Glass Mosaic	●			●		
Stone						●
Hard Bricks						
Cutting	●	●	●	●	●	●
Grinding	●					
Bevelling	●					

## SPECIFICATIONS

	DPG125	DCDA125	DCDW125	DCDS125	DCDV125	DCW60
Blade Diameter	125mm / 5"	125mm / 5"	125mm / 5"	125mm / 5"	125mm / 5"	60mm
Bore Size	22.23mm / 7/8"	22.23mm / 7/8"	22.23mm / 7/8"	22.23mm / 7/8"	22.23mm / 7/8"	M14 Thread
Segment Width	30mm	10mm	10mm	7mm	10mm	6mm
Maximum RPM	12250RPM	12250RPM	12250RPM	12250RPM	12250RPM	10200RPM

-  = Ideal material for cutting
-  = Suitable material for cutting
-  = NOT suitable for cutting